



**RCOVxxSL**

**DESCRIPTION**

The RCOVxxSL is a surface mounted, hinged, lockable cover for a 12/24/48 relay Lighting Automation Panel; the complete assembly also includes one each of the following:

1. Interior (RINTERxxyy)
2. Power Supply (RPWRxxx)
3. TUB (RTUBxx)

Separating the modules simplifies installation. The tub can be mounted early to allow conduit installation and rough-in wiring. The interior, which includes the relays and terminations, simply slides into the tub. The lighting circuits and low voltage control wiring can be terminated and the cover installed.

**SPECIFICATIONS**

<b>Description</b>	Lighting Automation Panel Surface, Hinged, Lockable Cover
<b>Catalog #</b>	RCOV12SL RCOV24SL RCOV48SL
<b>Operating Environment</b>	0-55 Degrees C (32-131F) 0-95% RH, Non Condensing Non Corrosive atmosphere
<b>Catalog #</b>	<b>Weight</b>
RCOV12SL	8 lbs / 3.6 Kg
RCOV24SL	22 lbs / 9.1 Kg
RCOV48SL	32 lbs / 13.6 Kg
<b>Codes</b>	NEMA 1 Rated UL 916 Energy Management CSA Certified
<b>Finish</b>	Painted Gray ASA 6-1

Job Name: _____	Page: ____ of ____