



**RPHONEx**

**DESCRIPTION**

The Phone Override Option provides for the override of relays through a Touch-tone phone.

The RPHONE-x is available in a 1 or 2-line configuration. Up to 9 RPHONE-2's can be added in separate RDLPWR-1 or RCLOCK devices, providing up to 18 phone extensions.

The RPHONE-x can be programmed to enable or disable phone call answering, and enable or disable the use of the OFF code (digit '0'). These features can be programmed to track any relay in the system, or can simply be enabled or disabled. Also, these features can be programmed individually for either line of the two line RPHONE-2. Therefore, the "public" number might restrict the use of digit '0', while the "private" number might allow complete control.

By tracking a relay, the system allows the features to be scheduled. For example, during normal office hours, digit '0' ('off' function) might be restricted by scheduling the tracking relay OFF.

**SPECIFICATIONS**

<b>Description</b>	Telephone Override Card
<b>Catalog #</b>	<i>RPHONE-1</i> Single Line Telephone Card <i>RPHONE-2</i> 2-Line Telephone Card
<b>Operating Environment</b>	0-55 Degrees C (32-131F) 0-95% RH, Non Condensing Non Corrosive atmosphere
<b>Mounting</b>	RDLPWR-1 or RCLOCK
<b>Weight</b>	1 lb / .5 Kg
<b>Codes</b>	UL 916 Energy Management CSA Certified